

Confidea L-DIV/L-CIV

WIRED VOTING UNIT WITH CHANNEL SELECTOR

Art. 71.98.0104 / 71.98.0114



Confidea L-DIV



Confidea L-CIV

Description

The Confidea L-DIV and L-CIV wired unit combines a slim, contemporary design with superior sound quality resulting in an excellent intelligibility.

The units are interconnected using the daisy chain principle over Cat 5 network cabling with RJ45 connectors. The connectors are hidden in the base of the unit and the cables are held in place by two notches in the unit housing.

Setup can be accomplished in just a blink of an eye.

As input and output connections are interchangeable, installation is easy, fast and straightforward, reducing installation cost. It is the ideal system for frequently changing environments.

It allows the delegate of a conference to speak, request-to-speak, listen to the speaker in their native tongue and register their votes.

The units are equipped with a microphone On/Off or request-to-speak button, a single channel selector driving two headphone outputs, a channel selection information display and five voting buttons

The OLED information display indicates the selected channel number, the language abbreviation in ISO format and a volume bar.

The chairman unit comes with an additional priority, next-in-line and system volume adjustment button.



The Confidea L-DIV and L-CIV units have the capability selecting up to 28 (CE2500) or 58 (CPU5500) channels depending on the central control unit used.

For 5 button voting applications the dedicated Televic software suite can be used, allowing preparation of voting agenda, extended voting control, logging and result display.

A screw lock connector is provided to connect a removable microphone.

As the microphone is immune against typical disturbances of mobile phones, delegates can leave their device on during the meeting. (MIC 385L, to be ordered separately)

The Confidea L-DIV/CIV can be used in combination with an RF wireless delegate unit (Confidea DIV/CIV with article number 71.98.0004/71.98.0014). The wireless conference unit has the same look and feel as the Confidea L-DIV/CIV and uses a removable battery with an autonomy of 20 hours minimum.

Controls and Features

- Built-in high quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback.
- Microphone On/Off or request-to-speak button with two signalling LEDs
- Two headphone outputs
- One headphone volume adjustment
- One channel Up/Down adjustment
- OLED channel and headphone volume information display
- Five voting buttons
- The chairman version (CIV) comes with a priority, next-in-line and system volume adjustment button

Connectivity

- Two 3.5 mm jack plugs for headphones
- Two RJ45 connectors
- Screw lock socket to connect removable microphone

Specifications

Technical Data	
Audio quality	16 bit digital
Headphone load impedance	> 32 ohm < 1k ohm
Output power	16.5 mW / 32 ohm
Power Supply	48V, over Cat5 cable
Dimensions (mm)	230(w), 130(h), 60(d)
Weight (g)	460
Color	RAL9011
Part number	Confidea L-DIV 71.98.0104 Confidea L-CIV 71.98.0114

Accessories

- Removeable microphone MIC38SL 71.98.0050
 - Headphones TEL151 71.04.0151
 - Digital bus cable, Cat5 24AWG:
 - 2m ICC5/2 71.60.4002
 - 5m ICC5/5 71.60.4005
 - 10m ICC5/10 71.60.4010
 - 20m ICC5/20 71.60.4020
- Standard Ethernet patch cable AWG26 cannot be used!
- SPL5525 for connection to TCS5500 central equipment 71.67.5035