



Product Overview:

This deceptively simple looking loop acts as a wireless connection to hearing aids equipped with a "T" coil. Listeners hook the loop into their wireless receiver, slip the loop around their neck, and the "T" coil picks up the sound and amplifies the transmitted sound into the ear.

Highlights:

- Use with any hearing aid equipped with a "T" coil
- Use with any Listen's receivers
- The receiver's antenna is built into the headphone cord

Includes:

One (1) LA-166 Neck Loop

Product Specification: Neck Loop	
Compliance	
Safety	RoHS
Standards	IEC 60118-4
Audio	
Frequency Response	20 Hz - 20 kHz
Impedance	12 ohm +/- 15% @ 1 kHz
Rated Power Input	75 mW
Max Power Input	2 W
Headset Input Sensitivity	110 dB +/- 4dB @ 1 kHz, 1 mW
Magnetic Field Strength	100 mA/m 6 inches above loop at 85µW 1kHz input (IEC 60118-4)
Loop	
Loop Cable Length	33 in. (84 cm)
Interconnections	

Connectors	3.5 mm Stereo
Physical	
Cable Length	22 in. (55 cm)
Color	Dark Grey
Dimensions (H x W x D)	1.44 in. x 1.10 in. x 0.59 in. (35 mm x 28 mm x 15 mm)
Weight	1.65 oz. (47 g)
Shipping Weight	1 lb. (0.5 kg)